



Technical Data Sheet

Q 70-420 Rallye Spray

Characteristics:

The ideal product for a fast, easy and cost optimised paint repair with the spray paint can. The fast drying product convinces through its easy handling and its universal usability with respect to the substrates (metal, steel metal sheet, plastics, etc.) as well as the application variety. Also qualified for non-automotive applications such as decorative paintings. Free of heavy metals: no lead, cadmium, chrome.

Application:

For use on objects made of sheet metal, metal and plastic.

For the upgrade and refurbishing of individual car parts.


Note:

Do not spray on surfaces coated with synthetic resins as the paint may lift.

Technical data:

Base: Nitro combination resin


Color: black matt (70-420-0401), black gloss (70-420-0402), black silk gloss (70-420-0403), white gloss (70-420-0404)




2 min.




clean surface



2x
40 - 50 µm




dust-dry ~ 20 min.
dry to touch ~ 40 min.
dry to paint ~ 60 min.




clean valve



MSDS



Shelf life



Store in cool place



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products.

Copyright: Q-Company 2017, all rights reserved.

Q-Company Int. GmbH / Beckershof 3 / D-24558 Henstedt-Ulzburg / Germany

Version: 02.01.2017