

---

<b>Product name</b>	:	<b>MoTip Car Care Tyre Repair</b>
<b>Article number</b>	:	<b>000712</b>
<b>Supplier / Producer</b>	:	<b>MOTIP DUPLI B.V.</b>
		<b>Wolfraamweg 2</b>
		<b>NL-8471 XC WOLVEGA</b>
		<b>Telephone number</b> +31 561 – 69 44 00
		<b>Telefax number</b> +31 561 – 69 44 31

---

### Product description

High quality rubber based spray to execute emergency repairs on tubeless tyres.

### Product characteristics

User-friendly  
Rubber based  
Can be used without removing the tyre

### Physical and Chemical Characteristics

Contents : 500 ml  
VOC-content : Approximately 50% w/w

### Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C.  
Before use, shake the aerosol.

Search the cause of the leakage and remove this. Completely let the tyre down. Screw the adaptor on the valve. Hold the can upside down and empty completely.

Drive approximately ten (10) kilometres with a maximum speed of 50 kilometre per hour in order to enable the product to equally spread in the tyre. Then remove the propellant from the tyre and again bring the tyre on pressure.

Repair the tyre soonest, indicating the tyre was temporarily repaired with Tyre Repair.

**Suitable to repair small leakages in the tread of the tyre.**

