






# Q 70-435

# Bumper Paint


## Characteristics


70-435 is a one-component textured coating to repair bumpers, trim strips, exterior mirrors etc. and to paint commonly used plastic substrates in the automotive industry Direct adhesion on cleaned and sanded plastic parts made of ABS, ABS-PC, PP-EPDM, PUR-RIM, PUR, hard PVC. Fast drying and easy application as well as good weather resistance are the characteristics of this product. Temperature-resistant up to 70 °C.

## Physical Characteristics

 **COLOR**  70-435-1001  70-435-1002


 12 month

 **VOC** 2004/42/IIB(e)(840)<539


 Thinner for 70-433 Bumper Paint, addition 10 - 15 %

## Application

 18 - 22 s  
4 mm DIN

 1,6 - 1,8 mm  
2,0 - 2,5 bar


 2

 1. 5 - 8 min.  
2. 10 - 15 min.


 40 - 50 µm

## Drying





 dust dry: 20 min  
set to touch: 60 min  
ready for assembly 24 h

## Storage

 Store the product in a ventilated place. Keep away from direct exposure to sunlight. Keep between +5°C and 20°C.

## Safety

 For more informations check the safety data sheet.

 This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.